

LINEAR AIR PUMPS



- Long lifetime ✓
- Robust aluminium construction ✓
- Minimum maintenance ✓
- Minimum energy consumption ✓

DB40, DB60, B80

DB120, DB150

DBMX80, DBMX100

Technical parameters of air pumps



Type	DB40	DB60	DB80	DB120	DB150	DBMX80	DBMX100
Pressure (mbar)	Air flow (l/min) [electrical consumption (Watt)]						
0	72 [45]	111 [69]	118 [92]	182 [165]	189 [184]	140 [109]	151 [126]
50	64 [45]	99 [68]	107 [93]	176 [136]	186 [181]	125 [107]	144 [125]
100	55 [44]	87 [65]	97 [92]	163 [126]	178 [175]	112 [100]	130 [119]
150	45 [40]	73 [61]	86 [88]	141 [118]	163 [168]	98 [93]	114 [112]
200	35 [36]	61 [56]	75 [83]	120 [108]	144 [157]	83 [88]	98 [102]
250	25 [31]	47 [49]	64 [77]	97 [96]	126 [142]	67 [83]	83 [92]
Optimum working pressure	< 250 mbar						

Voltage	230 V / 50 Hz						
Max. el.current (A)	0,44	0,62	0,98	1,27	1,98	0.63	0.82
Noise level (dB) – 1,5 m	37	39	40	53	53	50	50
Weight (kg)	6,5	7,3	7,6	12,4	12,8	7.5	7.5
Dimensions D x Š x V (mm)	205 x 172 x 210			336 x 212 x 187		261.5x215.4x222.5	
Conecting pipe	18			18		18	

Warranty 2 years for permanent duty , recomended every 12 months to change diaphragms

Distribution:

Eckold&Vavrouch, spol. s r.o.

www.eckold.cz

E-mail: eckold@volny.cz Tel: +420 5452 418 36

E-mail: mivalt.petr@post.cz Fax. +420 5452 115 82